### Piranha 2 P2-4x-xxx40 (10 μm)

Line Scan Cameras



#### **Key Features**

- 160 MHz throughput
- 10 µm pixels
- Resolutions from 2k to 4k
- High responsivity
- Medium Camera Link
- Single 12 V to 15 V power supply

#### Programmability

- Programmable pixel to pixel correction
- Adjustable analog and digital gain and offset
- 8 or 10 bit output
- Adjustable integration time and line rate
- Test pattern, line statistics, and camera diagnostics

#### **Typical Applications**

- Flat panel display inspection
- Printed circuit board inspection
- High performance document scanning/image lift
- Postal/parcel sorting

#### **Overview**

# Medium Camera Link, $10 \,\mu$ m pixels and resolution from 2k to 4k with proven performance.

Piranha 2 delivers superb performance with a wide selection of resolutions. Medium Camera Link with four 8 or 10 bit outputs at 40 MHz deliver 160 MHz throughput, and boosted responsivity means the Piranha 2 needs less light. Our 4 tap, 10  $\mu$ m models are available in resolutions from 2k to 4k.

The camera is small, light, and uses a single power supply. Cabling and interface are simplified with the Camera Link<sup>™</sup> high speed serial standard. The camera is very sensitive, but still provides quieter, more uniform output thanks to CDS (correlated double sampling) and embedded flat field correction algorithms. Gain and offset are fully programmable for each output channel, and the camera can output test patterns for cable/system troubleshooting.

#### Specifications

Resolution Data Rate Max. Line/Frame Rate Pixel Size Data Format Output Lens Mount Responsivity Dynamic Range Nominal Gain Range Size Mass **Operating Temp** Power Supply Power Dissipation **Regulatory Compliance** Control Data Power **Example Part Number** 


2048 / 4096 4 x 40 MHz 68 / 36 kHz  $10 \,\mu \text{m}$ 8. 10 bit Medium Camera Link 2k: M42 x 1, C, F mount / 4k: M72 x 0.75, F mount 76 DN/(nJ/cm<sup>2</sup>) @ 10 dB 54 dB  $\pm 10 \text{ dB}$ 85 mm x 85 mm x 53.7 mm <450 g 10 °C to 50 °C 12 V to 15 V <10 W CE MDR26 Camera Link Shared with Control Hirose HR10 6 pin P2-42-02K40




## Piranha 2 P2-4x-xxx40 (10 µm)

Line Scan Cameras

With established performance and wide customer base, the Piranha 2 is the camera generation known to have brought line scan performance to the next level.



CE




25.0

41.6 (2X

32.1 (2X)

7.5 (2X)

4K Camera





56.1



Worldwide Sales, 605 McMurray Rd, Waterloo, Ontario, Canada N2V 2E9 Tel: 1.519.886.6000 sales.americas@dalsa.com European Sales, Breslauer Str. 34, D-82194 Gröbenzell (Munich), Germany Tel: 49.8142.46770 sales.europe@dalsa.com Asia Pacific Sales, Ikebukuro East 13F, 3-4-3 Higashi-Ikebukuro, Toshimo-ku, Tokyo, 170-0013, Japan Tel: 81.3.5960.6353 sales.asia@dalsa.com

æ

M3x0.5 - 6H (4X) 5.0 DEPTH

70.0 (2X)